



## MOLD MAN 8000

- · Our most versatile machine
- Designed for production runs around 250,000 units per year
- Extremely user-friendly operation. No special training required to operate
- Mold up to four cavities at the same time (depending on part size)
- Fully independent adjustable process control
- Precisely meter shot sizes
- Accurately control flow rates
- Exact pressure control
- Patented permanent nozzle engagement for fewer moving parts
- Soft close safety feature



By far the best and simplest machine in its class.

# **MOLD MAN 8000** Product Specification Sheet

#### **Dimensions & Weight**

 Height
 1625 mm / 64.0"

 Width
 1040 mm / 41.0"

 Depth
 740 mm / 29"

 Weight
 430 kg / 950 lbs

### Power & Air Requirements

Voltage AC 208-230 V, Single Phase, 50/60 Hz

Power 4000 W

Air Pressure 8-10 bar / 115-145 psi Air Volume 120 lpm / 4 SCFM

#### **Standard Features**

Clamp Pneumatic
Clamping Force 10 kn / 1 ton
Clamp Stroke 150 mm / 6"
Ejector Pneumatic

Mold-set Dimension 200 mm x 150 mm / 8" x 6"
Injection Nozzle Permanent engagement
Mold-set Cooling Cross-drilled mold platens

Melt Reservoir 10 liter (10 kg) / 22 lbs self draining

Melt Temperature Up to  $245^{\circ}$  C /  $475^{\circ}$ F Injection Pressure 1-30 bar / 15-450 psi

Shot Size 0.5-100 grams / 0.02-3 ounces, typically Molding Cycle PLC controlled: standard or advanced

injection profiles

Operator Display Touch screen interface with all molding

parameters and cycle counter, customizable alarm screens, imperial or metric units

Safety Features Two-hand-no-tie-down actuation with

zero-force buttons, key lock for set-up or production mode, work table designed for easy mounting of custom fixtures, low initial clamping pressure, misplaced / foreign object sensing in clamping cycle, emergency-stop

palm button

Mold B an 08000 Options

Castor Kit Adds 127 mm / 5" to height. Kit includes

four castors with mounting hardware

Double Clamping Cylinder Increases the clamping force to 1.5 ton minimum

Mold-set Cooling Kit Kit includes chiller, hoses and fittings

Ideal for low to high volume production quantities